Anna Esposito Antonietta M. Esposito
Raffaele Martone Vincent C. Müller
Gaetano Scarpetta (Eds.)

LNCS 6456

Toward Autonomous, Adaptive, and Context-Aware Multimodal Interfaces

Theoretical and Practical Issues

Third COST 2102 International Training School
Caserta, Italy, March 2010
Revised Selected Papers

COST

EUCOG

Springer

Lecture Notes in Computer Science 6456

Commenced Publication in 1973
Founding and Former Series Editors:
Gerhard Goos, Juris Hartmanis, and Jan van Leeuwen

Editorial Board

David Hutchison
Lancaster University, UK

Takeo Kanade
Carnegie Mellon University, Pittsburgh, PA, USA

Josef Kittler
University of Surrey, Guildford, UK

Jon M. Kleinberg
Cornell University, Ithaca, NY, USA

Alfred Kobsa
University of California, Irvine, CA, USA

Friedemann Mattern
ETH Zurich, Switzerland

John C. Mitchell
Stanford University, CA, USA

Moni Naor
Weizmann Institute of Science, Rehovot, Israel

Oscar Nierstrasz
University of Bern, Switzerland

C. Pandu Rangan
Indian Institute of Technology, Madras, India

Bernhard Steffen
TU Dortmund University, Germany

Madhu Sudan
Microsoft Research, Cambridge, MA, USA

Demetri Terzopoulos
University of California, Los Angeles, CA, USA

Doug Tygar
University of California, Berkeley, CA, USA

Gerhard Weikum
Max Planck Institute for Informatics, Saarbruecken, Germany

Anna Esposito Antonietta M. Esposito
Raffaele Martone Vincent C. Müller
Gaetano Scarpetta (Eds.)

Toward Autonomous,

Adaptive, and Context-Aware Multimodal Interfaces

Theoretical and Practical Issues

Third COST 2102 International Training School
Caserta, Italy, March 15-19, 2010
Revised Selected Papers

13

Volume Editors

Anna Esposito
Second University of Naples
and IIASS, International Institute for Advanced Scientific Studies
Via Pellegrino 19, 84019 Vietri sul Mare (SA), Italy
E-mail: iiass.annaesp@tin.it

Antonietta M. Esposito
Istituto Nazionale di Geofisica e Vulcanologia, Osservatorio Vesuviano
Via Diocleziano 328, 80124 Napoli, Italy
E-mail: aesposito@ov.ingv.it

Raffaele Martone
Second University of Naples, Department of Engineering and Informatics
Via Roma 29, 81031 Aversa (CE), Italy
E-mail: raffaele.martone@unina2.it

Vincent C. Müller
Anatolia College/ACT, Department of Humanities and Social Sciences
Kennedy Street, 55510 Pylaia, Greece
E-mail: vmueller@act.edu

Gaetano Scarpetta
University of Salerno
and IIASS, International Institute for Advanced Scientific Studies
84081 Baronissi (SA), Italy
E-mail: scarpetta@fisica.unisa.it

ISSN 0302-9743 e-ISSN 1611-3349
ISBN 978-3-642-18183-2 e-ISBN 978-3-642-18184-9
DOI 10.1007/978-3-642-18184-9
Springer Heidelberg Dordrecht London New York

Library of Congress Control Number: 2010941945

CR Subject Classification (1998): H.5, H.5.2, I.2.7, H.3-4, I.2.10, J.1

LNCS Sublibrary: SL 3 – Information Systems and Application, incl. Internet/Web and HCI

© Springer-Verlag Berlin Heidelberg 2011
This work is subject to copyright. All rights are reserved, whether the whole or part of the material is concerned, specifically the rights of translation, reprinting, re-use of illustrations, recitation, broadcasting, reproduction on microfilms or in any other way, and storage in data banks. Duplication of this publication or parts thereof is permitted only under the provisions of the German Copyright Law of September 9, 1965, in its current version, and permission for use must always be obtained from Springer. Violations are liable to prosecution under the German Copyright Law.
The use of general descriptive names, registered names, trademarks, etc. in this publication does not imply, even in the absence of a specific statement, that such names are exempt from the relevant protective laws and regulations and therefore free for general use.

Typesetting: Camera-ready by author, data conversion by Scientific Publishing Services, Chennai, India

Printed on acid-free paper

Springer is part of Springer Science+Business Media (www.springer.com)

This book is dedicated to our needs,
that may overcome our goals and intentions one day,
though we resist.

Preface

This volume brings together the advanced research results obtained by the European COST Action 2102: "Cross Modal Analysis of Verbal and Nonverbal Communication." The research published in this book was discussed at the Third EUCOGII-COST 2102 International Training School entitled "Toward Autonomous, Adaptive, and Context-Aware Multimodal Interfaces: Theoretical and Practical Issues," held in Caserta, Italy, during March 15–19, 2010.

The school was jointly sponsored by:

a) COST (European Cooperation in Science and Technology, www.cost.eu) in the domain of Information and Communication Technologies (ICT) for disseminating the advances of the research activities developed within the COST Action 2102 (cost2102.cs.stir.ac.uk)
b) EUCogII: 2nd European Network for the Advancement of Artificial Cognitive Systems, Interaction and Robotics (http://www.eucognition.org/).

The school afforded a change of perspective in verbal and nonverbal communication, where the research focus moved from "communicative tools" to "communicative instances" and asked for investigations that, in modeling interaction, will take into account not only the verbal and nonverbal signals but also the internal and external environment, the context, and the cultural specificity in which communicative acts take place.

The consequences in information communication technology (ICT) research should result in the development of autonomous, adaptive, and context-aware multimodal interfaces able to act by exploiting instantiated contextual and environmental signals and process them by combining previous experience (memory) adapted to the communicative instance. This new approach will foster artificial cognitive research by creating a bridge between the most recent research in multimodal communication (taking into account gestures, emotions, social signal

processing etc.) and computation models that exploit these signals being aware of the context in which these signals are instantiated and of the internal and external environmental background. Human behavior exploits this information and adapts. Artificial cognitive systems must take account of this human ability for implementing a friendly and emotionally colored human machine interaction. In order to do this, investigations in cognitive computation must move from purely data-driven systems to behavioral systems able to "interact with human to achieve their goals," which may require ability to manifest intentions and goals through "resistance" to other intentions and goals (Müller argues in Chap. 1). In summary, cognitive models must be developed such that the current interactive dialogue systems, robots, and intelligent virtual avatars graphically embodied in

a 2D and/or 3D interactive virtual world, are able to interact intelligently with the environment, other avatars, and particularly with human users.

The themes of the papers presented in this book emphasize theoretical and practical issues for modelling cognitive behavioral systems, ranging from the attempts to describe brain computer interface (BCI) applications, a context-based approach to the interpretation and generation of dialogue acts, close synchronization among both speakers and listeners, mutual ratification, interaction and resistance, embodiment, language and multimodal cognition, timing effects on perception, action, and behaviors.

The book is arranged in two scientific sections according to a rough thematic classification, even though both sections are closely connected and both provide fundamental insights for the cross-fertilization of different disciplines.

The first section, "Human–Computer Interaction: Cognitive and Computational Issues," deals with conjectural and processing issues of defining models, algorithms, and strategies for implementing cognitive behavioral systems. The second section, "Synchrony Through Verbal and Nonverbal Signals," presents original studies that provide theoretical and practical solutions to the modelling of timing synchronization between linguistic and paralinguistic expressions, actions, body movements, activities in human interaction and on their assistance for an effective communication.

The papers included in this book benefited from the live interactions among the many participants of the successful meeting in Caserta. Over 150 established and apprenticing researchers converged for the event.

The editors would like to thank the Coordination Council of EUCogII and the ESF COST- ICT Programme for the support in the realization of the school and the publication of this volume. Acknowledgements go in particular to the COST Science Officers Matteo Razzanelli, Aranzazu Sanchez, Jamsheed Shorish, and the COST 2102 rapporteur Guntar Balodis for their constant help, guidance, and encouragement. Appreciation goes to the COST Publication Office for supporting and guiding the publication effort. The event owes its success to more individuals than can be named, but notably the members of the local Steering Committee Alida Labella, Olimpia Matarazzo, Nicola Melone, Giovanna Nigro, Augusto Parente, Paolo Pedone, Francesco Piazza, and Luigi Trojano who supported and encouraged the initiative as well as to the staff members Hicham Atassi, Ivana Baldassarre, Domenico Carbone, Vincenzo Capuano, Francesco Alessandro Conventi, Mauro De Vito, Davide Esposito, Paolo Fioretto, Marco

Grassi, and Gianluigi Ombrato who were actively involved in the success of the event. Special appreciation goes to the International Institute for Advanced Scientific Studies (IIASS), with a special mention to the memory of Maria Marinaro, and to the IIASS team Tina Marcella Nappi, Michele Donnarumma, and Antonio Natale who provided precious technical support in the organization of the school. The editors are deeply indebted to Maria Teresa Riviello for the wonderful work done in taking care of the local organization.

In addition, the editors are grateful to the contributors for making this book a scientifically stimulating compilation of new and original ideas. Finally, the editors would like to express their greatest appreciation to all the members of the COST 2102 International Scientific Committee for their rigorous and invaluable scientific revisions, their dedication, and their priceless selection process.

Anna Esposito
Antonietta M. Esposito
Raffaele Martone
Vincent C. Müller
Gaetano Scarpetta

Organization

International Steering Committee

Anna Esposito	Second University of Naples and IIASS, Italy
Marcos Faundez-Zanuy	Escola Universitaria Politecnica de Mataro, Spain
Amir Hussain	University of Stirling, UK
Raffaele Martone	Second University of Naples and IIASS, Italy
Nicola Melone	Second University of Naples and IIASS, Italy

COST 2102 International Scientific Committee

Samer Al Moubayed	Royal Institute of Technology, Sweden
Uwe Altmann	Technische Universität Dresden, Germany
Sigrún María Ammendrup	School of Computer Science, Reykjavik, Iceland
Hicham Atassi	Brno University of Technology, Czech Republic
Nikos Avouris	University of Patras, Greece
Ruth Bahr	University of South Florida, USA
Gérard Bailly	GIPSA, GRENOBLE, France
Marena Balinova	University of Applied Sciences, Vienna, Austria
Marian Bartlett	University of California, San Diego, USA
Dominik Bauer	RWTH Aachen University, Germany
Štefan Beňuš	Constantine the Philosopher University, Nitra, Slovakia
Niels Ole Bernsen	University of Southern Denmark, Denmark
Jonas Beskow	Royal Institute of Technology, Sweden
Peter Birkholz	RWTH Aachen University, Germany
Horst Bishof	Technical University Graz, Austria

Jean-Francois Bonastre	Universitè d'Avignon, France
Nikolaos Bourbakis	ITRI, Wright State University, Dayton, USA
Maja Bratanić	University of Zagreb, Croatia
Antonio Calabrese	Istituto di Cibernetica - CNR, Naples, Italy
Erik Cambria	University of Stirling, UK
Paola Campadelli	Università di Milano, Italy
Nick Campbell	University of Dublin, Ireland
Valentín Cardeñoso Payo	Universidad de Valladolid, Spain
Antonio Castro-Fonseca	Universidade de Coimbra, Portugal
Aleksandra Cerekovic	Faculty of Electrical Engineering , Croatia
Josef Chaloupka	Technical University of Liberec, Czech Republic

Mohamed Chetouani	Universitè Pierre et Marie Curie, France
Gérard Chollet	CNRS URA-820, ENST, France
Simone Cifani	Università Politecnica delle Marche, Italy
Muzeyyen Ciyiltepe	Gulhane Askeri Tip Academisi, Ankara, Turkey
Anton Cizmar	Technical University of Kosice, Slovakia
Nicholas Costen	Manchester Metropolitan University, UK
Francesca D'Olimpio	Second University of Naples, Italy
Vlado Delić	University of Novi Sad, Serbia
Giuseppe Di Maio	Second University of Naples, Italy
Marion Dohen	ICP, Grenoble, France
Thierry Dutoit	Faculté Polytechnique de Mons, Belgium
Laila DybkjÆr	University of Southern Denmark, Denmark
Jens Edlund	Royal Institute of Technology, Sweden
Matthias Eichner	Technische Universität Dresden, Germany
Aly El-Bahrawy	Ain Shams University, Cairo, Egypt
Engin Erzin	Koc University, Istanbul, Turkey
Anna Esposito	Second University of Naples, Italy
Joan Fàbregas Peinado	Escola Universitaria de Mataro, Spain
Sascha Fagel	Technische Universität Berlin, Germany
Nikos Fakotakis	University of Patras, Greece
Manuela Farinosi	University of Udine, Italy
Marcos Faúndez-Zanuy	Universidad Politécnica de Cataluña, Spain
Dilek Fidan	Ankara Universitesi, Turkey
Leopoldina Fortunati	Università di Udine, Italy
Todor Ganchev	University of Patras, Greece
Carmen García-Mateo	University of Vigo, Spain
Augusto Gnisci	Second University of Naples, Italy
Milan Gnjatović	University of Novi Sad, Serbia
Bjorn Granstrom	Royal Institute of Technology, Sweden
Marco Grassi	Università Politecnica delle Marche, Italy
Maurice Grinberg	New Bulgarian University, Bulgaria
Jorge Gurlekian	LIS CONICET, Buenos Aires, Argentina
Mohand-Said Hacid	Universite Claude Bernard Lyon 1, France
Jaakko Hakulinen	University of Tampere, Finland
Ioannis Hatzilygeroudis	University of Patras, Greece

Immaculada Hernaez University of the Basque Country, Spain
Javier Hernando Technical University of Catalonia, Spain
Wolfgang Hess Universität Bonn, Germany
Dirk Heylen University of Twente, The Netherlands
Daniel Hládek Technical University of Košice, Slovak Republic
Rüdiger Hoffmann Technische Universität Dresden, Germany
Hendri Hondorp University of Twente, The Netherlands

David House Royal Institute of Technology, Sweden Evgenia Hristova New Bulgarian University, Sofia, Bulgaria Stephan Hübler Dresden University of Technology, Germany Isabelle Hupont Aragon Institute of Technology, Zaragoza, Spain Amir Hussain University of Stirling, UK
Ewa Jarmolowicz Adam Mickiewicz University, Poznan, Poland
Kristiina Jokinen University of Helsinki, Finland
Jozef Juhár Technical University Košice, Slovak Republic
Zdravko Kacic University of Maribor, Slovenia
Bridget Kane Trinity College Dublin, Ireland
Jim Kannampuzha RWTH Aachen University, Germany
Maciej Karpinski Adam Mickiewicz University, Poznan, Poland
Eric Keller Université de Lausanne, Switzeland
Adam Kendon University of Pennsylvania, USA
Stefan Kopp University of Bielefeld, Germany
Jacques Koreman University of Science and Technology, Norway
Theodoros Kostoulas University of Patras, Greece
Maria Koutsombogera Inst. for Language and Speech Processing, Greece
Robert Krauss Columbia University, New York, USA
Bernd Kröger RWTH Aachen University, Germany
Gernot Kubin Graz University of Technology, Austria
Olga Kulyk University of Twente, The Netherlands
Alida Labella Second University of Naples, Italy
Emilian Lalev New Bulgarian University, Bulgaria
Yiannis Laouris Cyprus Neuroscience and Technology Institute, Cyprus
Anne-Maria Laukkanen University of Tampere, Finland
Borge Lindberg Aalborg University, Denmark
Saturnino Luz Trinity College Dublin, Ireland
Wojciech Majewski Wroclaw University of Technology, Poland
Pantelis Makris Neuroscience and Technology Institute, Cyprus
Raffaele Martone Second University of Naples, Italy
Rytis Maskeliunas Kaunas University of Technology, Lithuania
Dominic Massaro University of California - Santa Cruz, USA
Olimpia Matarazzo Second University of Naples, Italy
Christoph Mayer Technische Universität München, Germany
David McNeill University of Chicago, USA
Nicola Melone Second University of Naples, Italy
Katya Mihaylova University of National and World Economy, Sofia Bulgaria

Michal Mirilovič Technical University of Košice, Slovakia
Helena Moniz INESC-ID, Lisbon, Portugal

Peter Murphy University of Limerick, Ireland
Antonio Natale University of Salerno and IIASS, Italy
Eva Navas Escuela Superior de Ingenieros, Bilbao, Spain
Delroy Nelson University College London, UK
Géza Németh University of Technology and Economics, Budapest, Hungary
Friedrich Neubarth Austrian Research Inst. Artificial Intelligence, Austria
Christiane Neuschaefer-Rube RWTH Aachen University, Germany
Giovanna Nigro Second University of Naples, Italy
Anton Nijholt Universiteit Twente, The Netherlands
Jan Nouza Technical University of Liberec, Czech Republic
Stanislav Ondáš Technical University of Košice, Slovak Republic
Rieks Op den Akker University of Twente, The Netherlands
Igor Pandzic Faculty of Electrical Engineering, Zagreb, Croatia
Harris Papageorgiou Institute for Language and Speech Processing, Greece
Kinga Papay University of Debrecen, Hungary
Paolo Parmeggiani Università degli Studi di Udine, Italy
Ana Pavia Spoken Language Systems Laboratory, Portugal
Paolo Pedone Second University of Naples, Italy
Tomislav Pejsa University of Zagreb, Croatia
Catherine Pelachaud Université de Paris, France
Bojan Petek University of Ljubljana, Slovenia
Harmut R. Pfitzinger University of Munich, Germany
Francesco Piazza Università degli Studi di Ancona, Italy
Neda Pintaric University of Zagreb, Croatia
Matúš Pleva Technical University of Košice, Slovak Republic
Isabella Poggi Università di Roma 3, Italy
Ken Prepin Telecom-ParisTech, France
Jiří Přibil Academy of Sciences, Czech Republic
Anna Přibilová
Slovak University of Technology, Slovakia
Emanuele Principi Università Politecnica delle Marche, Italy
Michael Pucher Telecommunications Research Center Vienna, Austria
Jurate Puniene Kaunas University of Technology, Lithuania
Kari-Jouko Räihä University of Tampere, Finland
Roxanne Raine University of Twente, The Netherlands
Giuliana Ramella Istituto di Cibernetica - CNR, Naples, Italy
Fabian Ramseyer University Hospital of Psychiatry, Bern, Switzerland
Josè Rebelo Universidade de Coimbra, Portugal

Peter Reichl	FTW Telecommunications Research Center, Austria
Luigi Maria Ricciardi	Università di Napoli "Federico II", Italy
Maria Teresa Riviello	Second University of Naples and IIASS, Italy
Matej Rojc	University of Maribor, Slovenia
Nicla Rossini	Università del Piemonte Orientale, Italy
Rudi Rotili	Università Politecnica delle Marche, Italy
Algimantas Rudzionis	Kaunas university of Technology, Lithuania
Vytautas Rudzionis	Kaunas University of Technology, Lithuania
Hugo L. Rufiner	Universidad Nacional de Entre Ríos, Argentina
Milan Rusko	Slovak Academy of Sciences, Slovak Republic
Zsófia Ruttkay	Pazmany Peter Catholic University, Hungary
Yoshinori Sagisaka	Waseda University, Tokyo, Japan
Bartolomeo Sapio	Fondazione Ugo Bordoni, Rome, Italy
Mauro Sarrica	University of Padova, Italy
Gaetano Scarpetta	University of Salerno and IIASS, Italy
Silvia Scarpetta	Salerno University, Italy
Ralph Schnitker	Aachen University, Germany
Jean Schoentgen	Université Libre de Bruxelles, Belgium
Milan Sečujski	University of Novi Sad, Serbia
Stefanie Shattuck-Hufnagel	MIT, Research Laboratory of Electronics, USA
Marcin Skowron	Austrian Research Institute for Artificial Intelligence, Austria
Zdenek Smékal	Brno University of Technology, Czech Republic
Stefano Squartini	Università Politecnica delle Marche, Italy
Piotr Staroniewicz	Wroclaw University of Technology, Poland
Vojtěch Stejskal	Brno University of Technology, Czech Republic
Marian Stewart-Bartlett	University of California, San Diego, USA
Jin Su	Trinity College Dublin, Ireland
Dávid Sztahó	Budapest University of Technology and Economics, Hungary
Jianhua Tao	Chinese Academy of Sciences, P. R. China
Jure F. Tasič	University of Ljubljana, Slovenia
Murat Tekalp	Koc University, Istanbul, Turkey
Kristinn Thórisson	Reykjavík University, Iceland
Isabel Trancoso	Spoken Language Systems Laboratory, Portugal
Luigi Trojano	Second University of Naples, Italy
Wolfgang Tschacher	University of Bern, Switzerland
Markku Turunen	University of Tampere, Finland
Henk Van den Heuvel	Radboud University Nijmegen, The Netherlands
Leticia Vicente-Rasoamalala	Alchi Prefectural University, Japan

Robert Vich	Academy of Sciences, Czech Republic
Klára Vicsi	Budapest University, Hungary
Hannes Högni Vilhjálmsson	Reykjavík University, Iceland
Jane Vincent	University of Surrey, Guildford, UK
Carl Vogel	University of Dublin, Ireland
Jan Volín	Charles University, Czech Republic
Rosa Volpe	Université De Perpignan, France
Martin Vondra	Academy of Sciences, Czech Republic
Yorick Wilks	University of Sheffield, UK
Matthias Wimmer	Institute for Informatics, Munich, Germany
Matthias Wolf	Technische Universität Dresden, Germany
Bencie Woll	University College London, UK
Bayya Yegnanarayana	International Institute of Information Technology, India
Jerneja Žganec Gros	Alpineon, Development and Research, Slovenia
Goranka Zoric	Faculty of Electrical Engineering, Zagreb, Croatia

Sponsors

The following organizations sponsored and supported the International Training School:

- European COST Action 2102 "Cross-Modal Analysis of Verbal and Nonver- bal Communication" (cost2102.cs.stir.ac.uk)

COST—the acronym for European Cooperation in Science and Technology—is the oldest and widest European intergovernmental network for cooperation in research. Established by the Ministerial Conference in November 1971, COST is presently used by the scientific communities of 36 European countries to cooperate in common research projects supported by national funds.

The funds provided by COST—less than 1 of the total value of the projects—support the COST cooperation networks (COST Actions) through which, with EUR 30 million per year, more than 30,000 European scientists are involved in research having a total value which exceeds EUR 2 billion per year. This is the financial worth of the European added value which COST achieves.

A "bottom – Up approach" (the initiative of launching a COST Action comes from the European scientists themselves), "à la carte participation" (only countries interested in the Action participate), "equality of access" (participation is open also to the scientific communities of countries not belonging to the European Union) and "flexible structure" (easy implementation and light management of the research initiatives) are the main characteristics of COST.

As precursor of advanced multidisciplinary research, COST has a very important role for the realization of the European Research Area (ERA) anticipating and complementing the activities of the Framework Programmes, constituting a "bridge" towards the scientific communities of emerging countries, increasing the mobility of researchers across Europe and fostering the establishment of "Networks of Excellence" in many key scientific domains such as: biomedicine and molecular biosciences; food and agriculture; forests, their products and ser-

vices; materials, physical and nanosciences; chemistry and molecular sciences and technologies; earth system science and environmental management; information and communication technologies; transport and urban development; individuals, societies cultures and health. It covers basic and more applied research and also addresses issues of pre-normative nature or of societal importance. Web: http://www.cost.eu

- EUCogII: 2nd European Network for the Advancement of Artificial Cognitive Systems, Interaction and Robotics (http://www.eucognition.org/)
- Second University of Naples (www.unina2.it/), Faculty and Department of Psychology, Faculty of Science, Mathematics, and Physics and Department of Computer Engineering & Informatics, Italy

XVIII Sponsors

- International Institute for Advanced Scientific Studies "E.R. Caianiello" (IIASS, www.iiassvietri.it/), Italy
- Società Italiana Reti Neuroniche (SIREN, www.associazionesiren.org/)
- Regione Campania, Italy
- Provincia di Salerno, Italy

ESF Provide the COST Office through and EC contract

COST is supported by the EU RTD Framework programme

Table of Contents

I - Human-Computer Interaction: Cognitive and Computational Issues

Interaction and Resistance: The Recognition of Intentions in New Human-Computer Interaction 1
Vincent C. Müller

Speaking without Thinking: Embodiment, Speech Technology and Social Signal Processing 8
Tim Rohrer

More Than Words: Inference of Socially Relevant Information from Nonverbal Vocal Cues in Speech 23
Alessandro Vinciarelli, Hugues Salamin, Gelareh Mohammadi, and Khiet Truong

A Timely Endeavor: Theoretical, Behavioral, Bioimaging, and Clinical Perspectives on Time Perception 34
Argiro Vatakis and Georgios Papadelis

Instruction and Belief Effects on Sentential Reasoning 39
Olimpia Matarazzo and Ivana Baldassarre

Audio-Visual Prosody: Perception, Detection, and Synthesis of Prominence 55
Samer Al Moubayed, Jonas Beskow, Björn Granström, and David House

Adaptation in Turn-Initiations 72
Štefan Beňuš

Sentic Avatar: Multimodal Affective Conversational Agent with Common Sense 81
Erik Cambria, Isabelle Hupont, Amir Hussain, Eva Cerezo, and Sandra Baldassarri

Patterns of Synchronization of Non-verbal Cues and Speech in ECAs: Towards a More "Natural" Conversational Agent 96
Nicla Rossini

Top-Down Influences on Eye-Movements during Painting Perception: The Effect of Task and Titles 104
Evgenia Hristova, Severina Georgieva, and Maurice Grinberg

Visual Sociology in the Classroom: Fostering Interaction Awareness Using Video 116
Paolo Parmeggiani

Analysis of Interrogatives in Different Domains 134
Helena Moniz, Fernando Batista, Isabel Trancoso, and Ana Isabel Mata

Interviewers' Use of Coercive Questioning during a Midterm Period Favorable to the Opposition Party 147
Angiola Di Conza, Augusto Gnisci, and Angelo Caputo

Emotions and Speech Disorders: Do Developmental Stutters Recognize Emotional Vocal Expressions? 155
Anna Esposito and Alda Troncone

Representing Meaning in Mind: When Predicate Argument Structures

Meet Mental Representations 165
Rosa Volpe

Beyond the Panopticon Framework: Privacy, Control and User Generated Content 180
Manuela Farinosi

Micro and Macro Spatial Dimensions of New Media in Five European Countries 190
Leopoldina Fortunati and Federico de Luca

Nonverbal Expressions of Turn Management in TV Interviews: A Cross-Cultural Study between Greek and Icelandic 207
Maria Koutsombogera, Sigrún María Ammendrup, Hannes Högni Vilhjálmsson, and Harris Papageorgiou

II - Synchrony through Verbal and Nonverbal Signals

Interpretation and Generation of Dialogue with Multidimensional Context Models 214
Harry Bunt

Coordination, Not Control, Is Central to Movement 243
Fred Cummins

Speech, Gaze and Head Motion in a Face-to-Face Collaborative Task . . . 256
Sascha Fagel and Gérard Bailly

Neuroelectric Methodologies for the Study of the Economic Decisions in Humans 265
Giovanni Vecchiato and Fabio Babiloni

An Evaluation Study on Speech Feature Densities for Bayesian Estimation in Robust ASR 283
Simone Cifani, Emanuele Principi, Rudy Rotili, Stefano Squartini, and Francesco Piazza

Naturalness, Adaptation and Cooperativeness in Spoken Dialogue Systems 298
Milan Gnjatović, Darko Pekar, and Vlado Delić

Towards Semantic Multimodal Video Annotation 305
Marco Grassi, Christian Morbidoni, and Francesco Piazza

The Effect of Subharmonic Stimuli on Singing Voices 317
Marena Balinova, Peter Reichl, Inma Hernáez Rioja, and Ibon Saratxaga

Speech Modeling Using the Complex Cepstrum 324
Martin Vondra and Robert Vích

Problems of the Automatic Emotion Recognitions in Spontaneous Speech; An Example for the Recognition in a Dispatcher Center 331
Klára Vicsi and Dávid Sztahó

Slovak Language Model from Internet Text Data 340
Ján Staš, Daniel Hládek, Matúš Pleva, and Jozef Juhár

Automatic Recognition of Emotional State in Polish Speech 347
Piotr Staroniewicz

Categorical Perception of Consonants and Vowels: Evidence from a Neurophonetic Model of Speech Production and Perception 354
Bernd J. Kröger, Peter Birkholz, Jim Kannampuzha, and Christiane Neuschaefer-Rube

The MultiLis Corpus – Dealing with Individual Differences in Nonverbal Listening Behavior 362
Iwan de Kok and Dirk Heylen

Comparing the Rhythmical Characteristics of Speech and Music – Theoretical and Practical Issues 376
Stephan Hübler and Rüdiger Hoffmann

The Ability of Children with Mild Learning Disabilities to Encode Emotions through Facial Expressions 387
Christiane El-Haddad and Yiannis Laouris

Designing a Hungarian Multimodal Database – Speech Recording and Annotation 403
Kinga Papay

Conveying Directional Gaze Cues to Support Remote Participation in Hybrid Meetings 412
Betsy van Dijk, Job Zwiers, Rieks op den Akker, Olga Kulyk, Hendri Hondorp, Dennis Hofs, and Anton Nijholt

Affect Recognition in Real Life Scenarios 429
Theodoros Kostoulas, Todor Ganchev, and Nikos Fakotakis

Understanding Parent-Infant Behaviors Using Non-negative Matrix Factorization 436
Ammar Mahdhaoui and Mohamed Chetouani

Learning and Knowledge-Based Sentiment Analysis in Movie Review Key Excerpts 448
Björn Schuller and Tobias Knaup

Author Index 473

Sentic Avatar: Multimodal Affective Conversational Agent with Common Sense

Erik Cambria[1], Isabelle Hupont[2],
Amir Hussain[1], Eva Cerezo[3], and Sandra Baldassarri[3]

[1] University of Stirling, Stirling, UK
[2] Aragon Institute of Technology, Zaragoza, Spain
[3] University of Zaragoza, Zaragoza, Spain
{eca,ahu}@cs.stir.ac.uk,ihupont@ita.es,{sandra,ecerezo}@unizar.es
http://cs.stir.ac.uk/~eca/sentics

Abstract. The capability of perceiving and expressing emotions through different modalities is a key issue for the enhancement of human-computer interaction. In this paper we present a novel architecture for the development of intelligent multimodal affective interfaces. It is based on the integration of Sentic Computing, a new opinion mining and sentiment analysis paradigm based on AI and Semantic Web techniques, with a facial emotional classifier and Maxine, a powerful multimodal animation engine for managing virtual agents and 3D scenarios. One of the main distinguishing features of the system is that it does not simply perform emotional classification in terms of a set of discrete emotional labels but it operates in a continuous 2D emotional space, enabling the integration of the different affective extraction modules in a simple and scalable way.

Keywords: AI, Sentic Computing, NLP, Facial Expression Analysis, Sentiment Analysis, Multimodal Affective HCI, Conversational Agents.

1 Introduction

Emotions are a fundamental component in human experience, cognition, perception, learning and communication. A user interface cannot be considered really intelligent unless it is also capable of perceiving and expressing emotions. For this reason, affect sensing and recognition from multiple modalities is getting a more and more popular research field for the enhancement of human-computer interaction (HCI).

In this paper we present a novel architecture for integrating a process for reasoning by analogy over affective knowledge, a facial emotional classifier and a multimodal engine for managing 3D virtual scenarios and characters.

The structure of the paper is the following: Section 2 presents the state of the art of multimodal affective HCI, Section 3 briefly describes the proposed architecture, Section 4 explains in detail how the affect recognition and integration are performed and, eventually, Section 5 comprises concluding remarks and a description of future work.

A. Esposito et al. (Eds.): COST 2102 Int. Training School 2010, LNCS 6456, pp. 81–95, 2011.
© Springer-Verlag Berlin Heidelberg 2011

2 Multimodal Affective HCI

Human computer intelligent interaction is an emerging field aimed at providing natural ways for humans to use computers as aids. It is argued that for a computer to be able to interact with humans it needs to have the communication skills of humans. One of these skills is the affective aspect of communication, which is recognized to be a crucial part of human intelligence and has been argued to be more fundamental in human behaviour and success in social life than intellect [1][2]. Emotions influence cognition, and therefore intelligence, especially when it involves social decision-making and interaction.

The latest scientific findings indicate that emotions play an essential role in decision-making, perception, learning and more. Most of the past research on affect sensing has considered each sense such as vision, hearing and touch in isolation. However, natural human-human interaction is multimodal: we communicate through speech and use body language (posture, facial expressions, gaze) to express emotion, mood, attitude, and attention.

Affect recognition from multiple modalities has a short historical background and is still in its first stage [3]. It was not till 1998 that computer scientists attempted to use multiple modalities for recognition of emotions/affective states [4]. The results were promising: using multiple modalities improved the overall recognition accuracy helping the systems function in a more efficient and reliable way. Following the findings in psychology, which suggested that the most significant channel for judging emotional cues of humans is the visual channel of face and body [5], a number of works combine facial expressions and body gestures for affect sensing [6][7][8]. Other approaches combine different biological information such as brain signals or skin conductivity for affect sensing [9][10].

However this research makes use of a single information channel, i.e. a single type of computer input device, and, therefore, must assume the reliability on this channel. For that reason, the trend in recent works is to consider and combine affective information coming from different channels. That way, eventual changes on the reliability of the different information channels are considered.

Recent literature on multimodal affect sensing is focused on the fusion of data coming from the visual and audio channels. Most of those works make use of the visual channel for body gesture recognition [11] or facial expression classification [12] and the audio channel to analyze non-linguistic audio cues such as laughters [13], coughs [14] or cries [15]. However, very few works fuse information coming from the visual channel with linguistic-based (speech contents) audio affect sensing. With all these new areas of research in affect sensing, a number of challenges have arisen. In particular, the synchronization and fusion of the information coming from different channels is a big problem to solve.

Previous studies fused emotional information either at a decision-level, in which the outputs of the unimodal systems are integrated by the use of suitable expert criteria [16], or at a feature-level, in which the data from both modalities are combined before classification [17]. In any case, the choice of fusion strategy depends on the targeted application.

Accordingly, all available multimodal recognizers have designed and/or used ad-hoc solutions for fusing information coming from multiple modalities but cannot accept new modalities without re-defining the whole system. In summary, there is not a general consensus when fusing multiple modalities and systems' scalability is not possible.

3 Overview of the System

The architecture proposed (illustrated in Fig. 1) is based on the multimodal animation engine Maxine [18], and it consists of four main modules: Perception, Affective Analysis, Deliberative/Generative and Motor module.

The Perception module simply consists of the hardware necessary to gather the multimodal information from the user i.e. keyboard, microphone and web-cam. The Affective Analysis module aims to infer the user's affective state from the different inputs and integrate it. The Deliberative/Generative module is in charge of processing the extracted emotional information to manage the virtual agent's decisions and reactions, which are finally generated by the Motor module. In this paper we focus on the presentation of the affective sensing part of the system, explained in detail in Section 4.



Fig. 1. Sentic Avatar's architecture

4 Affective Analysis Module

The Affective Analysis Module is in charge of extracting emotions from the textual, vocal and video inputs and integrate them.

It consists of three main parts: Sentic Computing, for inferring emotions from typed-in text and speech-to-text converted contents (Section 4.1), Facial Expression Analyzer, for extracting affective information from video (Section 4.2), and Affective Integrator, for integrating the outputs coming from the two previous modules (Section 4.3).

4.1 Sentic Computing

Sentic Computing [19] is a new opinion mining and sentiment analysis paradigm which exploits AI and Semantic Web techniques to better recognize, interpret and process opinions and sentiments in natural language text.

In Sentic Computing, whose term derives from the Latin 'sentire' (the root of words such as sentiment and sensation) and 'sense' (intended as common sense), the analysis of text is not based on statistical learning models but rather on common sense reasoning tools [20] and domain-specific ontologies [21]. Differently from keyword spotting [22][23][24], lexical affinity [25][26] and statistical [27][28][29] approaches, which generally requires large inputs and thus cannot appraise texts with satisfactory granularity, Sentic Computing enables the analysis of documents not only on the page or paragraph-level but also on the sentence-level.

AffectiveSpace. AffectiveSpace [30] is a multi-dimensional vector space built from ConceptNet [31], a semantic network of common sense knowledge, and WordNet-Affect, a linguistic resource for the lexical representation of affective knowledge [32]. The blend [33] of these two resources yields a new dataset in which common sense and affective knowledge coexist i.e. a 14,301 $\times$ 117,365 matrix whose rows are concepts (e.g. 'dog' or 'bake cake'), whose columns are either common sense and affective features (e.g. 'isA-pet' or 'hasEmotion-joy'), and whose values indicate truth values of assertions.

In this knowledge base each concept is represented by a vector in the space of possible features whose values are positive for features that produce an assertion of positive valence (e.g. 'a penguin is a bird'), negative for features that produce an assertion of negative valence (e.g. 'a penguin cannot fly') and zero when nothing is known about the assertion. The degree of similarity between two concepts, then, is the dot product between their rows in the blended matrix.

The value of such a dot product increases whenever two concepts are described with the same feature and decreases when features that are negations of each other describe them. When performed on the blended matrix, however, these dot products have very high dimensionality (as many dimensions as there are features) and are difficult to work with. In order to approximate these dot products in a useful way, we project all of the concepts from the space of features into a space with many fewer dimensions i.e. we reduce the dimensionality of the matrix by means of principal component analysis (PCA).

In particular, we perform truncated singular value decomposition (TSVD) [34] in order to obtain a new matrix that forms a low-rank approximation of the original data and represents, for the Eckart–Young theorem [35], the best estimation of the original data in the Frobenius norm sense. By exploiting the information sharing property of truncated SVD, concepts with the same affective valence are likely to have similar features – that is, concepts conveying the same emotion tend to fall near each other in AffectiveSpace. Concept similarity does not depend on their absolute positions in the vector space, but rather on the angle they make with the origin.



Fig. 2. A sketch of AffectiveSpace

For example we can find concepts such as 'beautiful day', 'birthday party', 'laugh' and 'make person happy' very close in direction in the vector space, while concepts like 'sick', 'feel guilty', 'be laid off' and 'shed tear' are found in a completely different direction (nearly opposite with respect to the center of the space). If we choose to discard all but the first 100 principal components, common sense concepts and emotions are represented by vectors of 100 coordinates: these coordinates can be seen as describing concepts in terms of 'eigenmoods' that form the axes of AffectiveSpace i.e. the basis $e_0,...,e_{99}$ of the vector space. For example, the most significant eigenmood, e_0, represents concepts with positive affective valence. That is, the larger a concept's component in the e_0 direction is, the more affectively positive it is likely to be. Concepts with negative e_0 components, then, are likely to have negative affective valence.

The Hourglass of Emotions. The Hourglass of Emotions is an affective categorization model developed starting from Plutchik's studies on human emotions [36]. In the model (illustrated in Fig. 3) sentiments are reorganized around four independent dimensions whose different levels of activation make up the total emotional state of the mind. The Hourglass of Emotions, in fact, is based on the idea that the mind is made of different independent resources and that emotional states result from turning some set of these resources on and turning another set of them off [37].

The model is particularly useful to recognize, understand and express emotions in the context of human-computer interaction (HCI). In the Hourglass of



	Pleasantness	Attention	Sensitivity	Aptitude
+3	ecstasy	vigilance	rage	admiration
+2	joy	anticipation	anger	trust
+1	serenity	interest	annoyance	acceptance
0	—	—	—	—
-1	pensiveness	distraction	apprehension	boredom
-2	sadness	surprise	fear	disgust
-3	grief	amazement	terror	loathing



Fig. 3. The Hourglass of Emotions

Emotions, in fact, affective states are not classified, as often happens in the field of emotion analysis, into a few basic categories, but rather into four concomitant but independent dimensions – Pleasantness, Attention, Sensitivity and Aptitude – in order to understand how much respectively:

1. the user is happy with the service provided
2. the user is interested in the information supplied
3. the user is comfortable with the interface
4. the user is disposed to use the application

Each affective dimension is characterized by six levels of activation that determine the intensity of the expressed/perceived emotion, for a total of 24 labels specifying 'elementary emotions'. The concomitance of the different affective dimensions makes possible the generation of 'compound emotions' such as *love*, given by the combination of *joy* and *trust*, or *disappointment*, given by the concomitance of *surprise* and *sadness*.

Sentics Extraction Process. The text contents typed-in by the user and the dialogue contents, traslated into text using Loquendo automatic speech recognition (ASR) [38], go through a Natural Language Processing (NLP) module,



Fig. 4. Sentics Extraction Process

which performs a first skim of the document, a Semantic Parser, whose aim is to extract concepts from the processed text, and eventually AffectiveSpace, for the inference of concepts' affective valence (Fig. 4).

In particular, the NLP module interprets all the affective valence indicators usually contained in text such as special punctuation, complete upper-case words, onomatopoeic repetitions, exclamation words, degree adverbs or emoticons, and it ultimately lemmatizes text.

The Semantic Parser exploits a concept n-gram model extracted from ConceptNet graph structure in order to deconstruct text into common sense concepts. Once concepts are retrieved from the lemmatized text, the parser also provides, for each of these, the relative frequency, valence and status i.e. the concept's occurrence in the text, its positive or negative connotation, and the degree of intensity with which the concept is expressed.

The AffectiveSpace module, eventually, projects the retrieved concepts into the vector space clustered (using a k-means approach) wrt the Hourglass model, and infers the affective valence of these according to the positions they occupy in the multi-dimensional space.

Therefore, the outputs of the Sentics Extraction Process are four dimensional vectors, called 'sentic vectors', which specify the emotional charge carried by each concept in terms of Pleasantness, Attention, Sensitivity and Aptitude. This information is ultimately exploited to produce emotional labels which are given as inputs to the Affective Integrator, as shown in the example below:

Text: Yesterday was a BEAUTIFUL day!
I couldn't find the food I was after and there was pretty bad weather
but I bought a new dress and a lot of Christmas presents.

<Concept: 'yesterday'>
<Concept: 'beautiful day'++>

<Concept: !'find food'>
<Concept: 'bad weather'–>
<Concept: 'buy new dress'>
<Concept: 'buy christmas present'++>

Sentics: [1.608, 0.571, 0.0, 2.489]
Moods: joy and interest
Polarity: 0.51

4.2 Facial Expression Analyzer

The Facial Expression Analyzer achieves an automatic classification of the shown facial expressions into discrete emotional categories. It is able to classify the user's emotion in terms of Ekman's six universal emotions (*fear*, *sadness*, *joy*, *disgust*, *surprise* and *anger*) [39] plus *neutral*, giving a membership confidence value to each emotional category.

The face modeling selected as input for the Facial Expression Analyzer follows a feature-based approach: the inputs are a set of facial distances and angles calculated from feature points of the mouth, eyebrows and eyes. In fact, the inputs are the variations of these angles and distances with respect to the neutral face. The points are obtained thanks to a real-time facial feature tracking program [40].

Fig. 5(a) shows the correspondence of these points with those defined by the MPEG4 standard. The set of parameters obtained from these points is shown in Fig. 5(b). In order to make the distance values consistent (independently of the scale of the image, the distance to the camera, etc.) and independent of the expression, all the distances are normalized with respect to the distance between the eyes i.e. the MPEG4 Facial Animation Parameter Unit (FAPU), also called ESo. The choice of angles provides a size invariant classification and saves the effort of normalization. As regards the classification process itself, the system intelligently combines the outputs of 5 different classifiers simultaneously. In this way, the overall risk of making a poor selection with a given classifier for a given input is reduced.

The classifier combination chosen follows a weighted majority voting strategy, where the voted weights are assigned depending on the performance of each classifier for each emotion. In order to select the best classifiers to combine, the Waikado Environment for Knowledge Analysis (Weka) tool was used [41]. This provides a collection of machine learning algorithms for data mining tasks. From this collection, five classifiers were selected after tuning: RIPPER, Multilayer Perceptron, SVM, Naive Bayes and C4.5.

The selection was based on their widespread use as well as on the individual performance of their Weka implementation. To train the classifiers and evaluate the performance of the system, two different facial emotion databases were used: the FGNET database [42] that provides video sequences of 19 different Caucasian people, and the MMI Facial Expression Database [43] that holds 1280 videos of 43 different subjects from different races (Caucasian, Asian and Arabic). Both databases show Ekman's six universal emotions plus *neutral*.



(a) (b)

Fig. 5. (a) Tracked facial feature points according to MPEG4 standard and (b) corresponding facial parameters

Table 1. Confusion matrix obtained combining the five classifiers

classified as	disgust	joy	anger	fear	sadness	neutral	surprise
disgust	**79.41%**	0%	2.39%	18.20%	0%	0%	0%
joy	4.77%	**95.23%**	0%	0%	0%	0%	0%
anger	19.20%	0%	**74.07%**	0%	3.75%	2.98%	0%
fear	9.05%	0%	0%	**62.96%**	8.53%	0%	19.46%
sadness	0.32%	0.20%	1.68%	0%	**30.00%**	67.80%	0%
neutral	0%	0%	1.00%	2.90%	4.10%	**92.00%**	0%
surprise	0%	0%	0%	11.23%	0%	4.33%	**84.44%**

A new database has been built for testing this work with a total of 1500 static frames carefully selected from the apex of the video sequences from the FG-NET and MMI databases. The results obtained when applying the strategy explained previously to combine the scores of the five classifiers are shown in the form of confusion matrix in Table 1 (results have been obtained with a 10-fold cross-validation test over the 1500 database images).

As can be observed, the success rates for *neutral*, *joy* and *surprise* are very high (84.44%–95.23%). However, the system tends to confuse *disgust* with *fear*, *anger* with *disgust* and *fear* with *surprise*; therefore, the performances for those emotions are slightly worse. The lowest result of our classification is for *sadness*: it is confused with *neutral* on 67.80% of occasions, due to the similarity of the facial expressions. Confusion between these pairs of emotions occurs frequently in the literature and for this reason many classification works do not consider some of them. Nevertheless, the results can be considered positive as two incompatible emotions (such as *sadness* and *joy* or *fear* and *anger*) are confused on less

Table 2. Confusion matrix obtained after considering human assessment

classified as	disgust	joy	anger	fear	sadness	neutral	surprise
disgust	**84.24%**	0%	2.34%	13.42%	0%	0%	0%
joy	4.77%	**95.23%**	0%	0%	0%	0%	0%
anger	15.49%	0%	**77.78%**	0%	3.75%	2.98%	0%
fear	1.12%	0%	0%	**92.59%**	2.06%	0%	4.23%
sadness	0.32%	0.20%	1.68%	0%	**66.67%**	31.13%	0%
neutral	0%	0%	0%	0.88%	1.12%	**98.00%**	0%
surprise	0%	0%	0%	6.86%	0%	2.03%	**91.11%**

than 0.2% of occasions. Another relevant aspect to be taken into account when evaluating the results is human opinion.

The labels provided in the database for training classifiers correspond to the real emotions felt by users although they do not necessarily have to coincide with the perceptions other human beings may have about the facial expressions shown. Undertaking this kind of study is very important when dealing with human-computer interaction, since the system is proved to work in a similar way to the human brain. In order to take into account the human factor in the evaluation of the results, 60 persons were told to classify the 1500 images of the database in terms of emotions. As a result, each one of the frames was classified by 10 different persons in 5 sessions of 50 images.

The Kappa statistic obtained from raters annotations is equal to 0.74 (calculated following the formula proposed in [44]), which indicates an adequate inter-rater agreement in the emotional images annotation. With this information, the evaluation of the results was repeated: the recognition was marked as good if the decision was consistent with that reached by the majority of the human assessors. The results (confusion matrix) of considering users' assessment are shown in Table 2. As can be seen, the success ratios have considerably increased. Therefore, it can be concluded that the confusions of the algorithms go in the same direction as those of the users: our classification strategy is consistent with human classification.

4.3 Affective Integrator

The Sentics Extraction Process outputs a list of sentic vectors which represents an emotional analysis of text and dialogue contents in terms of Pleasantness, Attention, Sensitivity and Aptitude while the Facial Expression Analyzer provides an affective evaluation of video contents in terms of Ekman's six universal emotions. Some researchers, such as Whissell [45] and Plutchik [46], consider emotions as a continuous 2D space whose dimensions are evaluation and activation. The evaluation dimension measures how a human feels, from positive to negative. The activation dimension measures whether humans are more or less likely to take some action under the emotional state, from active to passive. To overcome the problem of the integration of the affective information coming from the Sentic Extraction



Fig. 6. Whissell's model

Process and the Facial Expression Analyzer, the continuous 2D description of affect is considered.

Bi-dimensional representations of affect are attractive mainly because they provide a way of describing emotional states that is more tractable than using words. This is of particular importance when dealing with naturalistic data, where a wide range of emotional states occurs. Similarly, they are much more able to deal with non discrete emotions and variations in emotional states over time, since in such cases changing from one universal emotion label to another would not make much sense in real life scenarios.

In her study, Cynthia Whissell assigns a pair of values activation-evaluation to each of the approximately 9000 words with affective connotations that make up her Dictionary of Affect in Language. Fig. 6 shows the position of some of these words in the activation-evaluation space.

The emotion-related words corresponding to each one of Ekman's six emotions plus *neutral* and to the levels of Pleasantness, Attention, Sensitivity and Aptitude have a specific location in the Whissell space. Thanks to this, in our work the output information of the Sentic Extraction Process and the labels provided by the Facial Expression Analyzer can be mapped in the Whissell space: a pair of values activation-evaluation can be calculated from the obtained labels, and hence concurrently visualized and compared in the 2D space (Fig. 7).



Fig. 7. Example of Affective Analysis Module output: integration of the extracted emotional information (from audio and video) into the Whissell space

In particular, the process of affective integration is achieved through the following three steps:

1. Each one of the emotional labels inferred by the Sentics Extraction Process from the video spoken sentence is mapped as a 2D point on to the Whissell space.
2. In the same way, the Facial Expression Analyzer outputs the user's emotion in terms of Ekman's six universal emotions (plus *neutral*), giving a membership confidence value to each emotional category. The mapping of its output in the Whissell space is carried out considering each of Ekman's six basic emotions plus *neutral* as 2D weighted points in the activation-evaluation space, where the weights are assigned depending on the confidence value obtained for each emotion in the classification process. The final detected emotion is calculated as the centre of mass of the seven weighted points in the Whissell space. That way, the Facial Expression analyzer outputs one emotional location in the Whissell space per frame of the studied video sequence.
3. Finally, the whole set of 2D activation-evaluation points obtained from both the Sentics Extraction Process and the Facial Expression Analyzer is fitted to the Minimum Volume Ellipsoid (MVE) that better covers the shape of the set of extracted points. The MVE is calculated following the algorithm described by Kumar and Yildrim [47]. The final emotional information outputted by affective analysis module for the whole video sequence is given by the x-y coordinates of the centre of that MVE.

5 Conclusion and Future Work

This paper describes a novel architecture for multimodal affective interaction with conversational agents. The proposed system recognizes user's affective state through two different modalities: AffectiveSpace, a process for reasoning by analogy and association over common sense and affective knowledge able to extract affective information in terms of Pleasantness, Attention, Sensitivity and Aptitude from spoken words (dialogue contents), and a Facial Expression Analyzer that classifies the shown user's facial expression in terms of the six Ekman's universal emotions (plus *neutral*).

The emotional information coming from these two different channels is integrated in a simple manner thanks to Whissell's 2D activation-evaluation space, where all the extracted emotional labels are mapped onto x-y locations of that space. The benefits of using Whissell 2D representation are, on the one hand, that the final output of the system does not simply provide a classification in terms of a set of emotionally discrete labels but goes further by extending the emotional information over an infinite range of intermediate emotions and, on the other hand, its capability for improving the overall recognition accuracy helping the system function in a more reliable way.

Furthermore, it opens the door to the integration of new emotional extraction modules in the future (e.g. modules that study user's gestures, gaze, mouse-clicks or keyboard use for affective recognition) in a simple and scalable fashion.

References

1. Vesterinen, E.: Affective Computing. In: Digital Media Research Seminar, Helsinki (2001)
2. Pantic, M.: Affective Computing. Encyclopedia of Multimedia Technology and Networking. Hershy 1, 8–14, Idea Group Reference (2005)
3. Gunes, M., Gunes, H., Piccardi, M., Pantic, M.: From the Lab to the Real World: Affect Recognition Using Multiple Cues and Modalities. In: Affective Computing: Focus on Emotion Expression, Synthesis and Recognition, pp. 185–218 (2008)
4. Riseberg, J., Klein, J., Fernandez, R., Picard, R.: Frustrating the User on Purpose: Using Biosignals in a Pilot Study to Detect the User's Emotional State. In: CHI, Los Angeles (1998)
5. Ambady, N., Rosenthal, R.: Thin Slices of Expressive Behavior as Predictors of Interpersonal Consequences: a Meta-Analysis. Psychological Bulletin 11(2), 256–274 (1992)
6. Camurri, A., Mazzarino, B., Volpe, G.: Analysis of Expressive Gesture: The EyesWeb Expressive Gesture Processing Library. In: Gesture Workshop, Genova (2003)
7. Gunes, H., Piccardi. M.: Bi-Modal Emotion Recognition from Expressive Face and Body Gestures. Network and Computer Applications 30(4), 1334–1345 (2007)
8. Karpouzis, K., Caridakis, G., Kessous, L., Amir, N., Raouzaiou, A., Malatesta, L., Kollias, S.: Modeling Naturalistic Affective States Via Facial, Vocal and Bodily Expressions Recognition. In: Huang, T.S., Nijholt, A., Pantic, M., Pentland, A. (eds.) ICMI/IJCAI Workshops 2007. LNCS (LNAI), vol. 4451, pp. 92–116. Springer, Heidelberg (2007)

9. Pun, T., Alecu, T., Chanel, G., Kronegg, J., Voloshynovskiy, S.: Brain-Computer Interaction Research at the Computer Vision and Multimedia Laboratory. IEEE Trans. on Neural Systems and Rehabilitation Engineering 14(2), 210–213 (2006)
10. Burleson, W., Picard, R., Perlin, K., Lippincott, J.: A Platform for Affective Agent Research. In: International Conference on Autonomous Agents and Multiagent Systems, New York (2004)
11. Petridis, S., Pantic, M.: Audiovisual Discrimination between Laughter and Speech. In: ICASSP, Las Vegas (2008)
12. Valstar, M., Gunes, H., Pantic, M.: How to Distinguish Posed from Spontaneous Smiles Using Geometric Features. In: ICMI, Nagoya (2007)
13. Truong, K., Van Leeuwen, D.: Automatic Discrimination Between Laughter and Speech. Speech Communication 49, 144–158 (2007)
14. Matos, S., Birring, S., Pavord, I., Evans, D.: Detection of Cough Signals in Continuous Audio Recordings Using HMM. IEEE Trans. on Biomedical Engineering 53(6), 1078–1083 (2006)
15. Pal, P., Iyer, A., Yantorno, R.: Emotion Detection from Infant Facial Expressions and Cries. In: Intl Conf. Acoustics, Speech and Signal Processing (2006)
16. Jong-Tae, J., Sang-Wook, S., Kwang-Eun, K., Kwee-Bo, S.: Emotion Recognition Method Based on Multimodal Sensor Fusion Algorithm. In: ISIS, Sokcho-City (2007)
17. Shan, C., Gong, S., McOwan, P.: Beyond Facial Expressions: Learning Human Emotion from Body Gestures. In: BMVC, Warwick (2007)
18. Baldassarri, S., Cerezo, E., Seron, F.: Maxine: a Platform for Embodied Animated Agents. Computers and Graphics 32(4), 430–437 (2008)
19. Cambria, E., Hussain, A., Havasi, C., Eckl, C.: Sentic Computing: Exploitation of Common Sense for the Development of Emotion-Sensitive Systems. In: Esposito, A., Campbell, N., Vogel, C., Hussain, A., Nijholt, A. (eds.) COST 2102. LNCS, vol. 5967, pp. 153–161. Springer, Heidelberg (2010)
20. Cambria, E., Hussain, A., Havasi, C., Eckl, C.: Common Sense Computing: From the Society of Mind to Digital Intuition and Beyond. In: Fierrez, J., Ortega-Garcia, J., Esposito, A., Drygajlo, A., Faundez-Zanuy, M. (eds.) BioID MultiComm 2009. LNCS, vol. 5707, pp. 252–259. Springer, Heidelberg (2009)
21. Cambria, E., Grassi, M., Hussain, A., Havasi, C.: Sentic Computing for Social Media Marketing. In: Multimedia Tools and Applications. Springer, Heidelberg (to appear, 2010)
22. Elliott, C.: The Affective Reasoner: A Process Model of Emotions in a Multi-Agent System. The Institute for the Learning Sciences, Technical Report No. 32 (1992)
23. Ortony, A., Clore, G., Collins, A.: The Cognitive Structure of Emotions. Cambridge University Press, New York (1988)
24. Wiebe, J., Wilson, T., Claire, C.: Annotating Expressions of Opinions and Emotions in Language. Language Resources and Evaluation 39(2), 165–210 (2005)
25. Wilson, T., Wiebe, J., Hoffmann, P.: Recognizing Contextual Polarity in Phrase-Level Sentiment Analysis. In: HLT-EMNLP, Vancouver (2005)
26. Somasundaran, S., Wiebe, J., Ruppenhofer, J.: Discourse Level Opinion Interpretation. In: COLING, Manchester (2008)
27. Hu, M., Liu, B.: Mining Opinion Features in Customer Reviews. In: AAAI, San Jose (2004)
28. Pang, B., Lee, L.: Seeing Stars: Exploiting Class Relationships for Sentiment Categorization with Respect to Rating Scales. In: ACL, Ann Arbor (2005)

29. Abbasi, A., Chen, H., Salem, A.: Sentiment Analysis in Multiple Languages: Feature Selection for Opinion Classification in Web Forums. ACM Transactions on Information Systems 26(3), 1–34 (2008)
30. Cambria, E., Hussain, A., Havasi, C., Eckl, C.: AffectiveSpace: Blending Common Sense and Affective Knowledge to Perform Emotive Reasoning. In: WOMSA at CAEPIA, Seville (2009)
31. Havasi, C., Speer, R., Alonso, J.: ConceptNet 3: a Flexible, Multilingual Semantic Network for Common Sense Knowledge. In: RANLP, Borovets (2007)
32. Strapparava, C., Valitutti, A.: WordNet-Affect: an Affective Extension of WordNet. In: LREC, Lisbon (2004)
33. Havasi, C., Speer, R., Pustejovsky, J., Lieberman, H.: Digital Intuition: Applying Common Sense Using Dimensionality Reduction. IEEE Intelligent Systems 24(4), 24–35 (2009)
34. Wall, M., Rechtsteiner, A., Rocha, L.: Singular Value Decomposition and Principal Component Analysis. In: Berrar, D., et al. (eds.) A Practical Approach to Microarray Data Analysis, pp. 91–109. Kluwer, Norwell (2003)
35. Eckart, C., Young, G.: The Approximation of One Matrix by Another of Lower Rank. Psychometrika 1(3), 211–218 (1936)
36. Plutchik, R.: The Nature of Emotions. American Scientist 89(4), 344–350 (2001)
37. Minsky, M.: The Emotion Machine. Simon and Schuster, New York (2006)
38. Loquendo Audio Speech Recognition, `http://www.loquendo.com`
39. Ekman, P., Dalgleish, T., Power, M.: Handbook of Cognition and Emotion. Wiley, Chihester (1999)
40. Cerezo, E., Hupont, I., Manresa, C., Varona, J., Baldassarri, S., Perales, F., Seron, F.: Real-Time Facial Expression Recognition for Natural Interaction. In: Martí, J., Benedí, J.M., Mendonça, A.M., Serrat, J. (eds.) IbPRIA 2007. LNCS, vol. 4478, pp. 40–47. Springer, Heidelberg (2007)
41. Witten, I., Frank, E.: Data Mining: Practical Machine Learning Tools and Techniques. Morgan Kaufmann, San Francisco (2005)
42. Wallhoff, F.: Facial Expressions and Emotion Database. Technische Universitat Munchen (2006)
43. Pantic, M., Valstar, M., Rademaker, R., Maat, L.: Web-Based Database for Facial Expression Analysis. In: ICME, Singapore (2005)
44. Siegel, S., Castellan, N.: Nonparametric Statistics for the Social Siences. McGraw-Hill, New York (1988)
45. Whissell, C.: The Dictionary of Affect in Language. Emotion: Theory, Research and Experience, The Measurement of Emotions 4, 113–131 (1989)
46. Plutchik, R.: Emotion: a Psychoevolutionary Synthesis. Harper and Row, New York (1980)
47. Kumar, P., Yildirim, E.: Minimum-Volume Enclosing Ellipsoids and Core Sets. Journal of Optimization Theory and Applications 126, 1–21 (2005)